

TH3020 is a temperature & humidity datalogger with accuracy of $\pm 0.3\%$. This device is featured with touch sensitive button and 3.9 inch LCD screen with backlight. It has Ultra low power consumption and long standby time. It displays real-time and historical alarm status indicator & maximum, minimum, average.

FEATURES

- Touch Sensitive button
- Accuracy $\pm 0.3\%$
- Human comfort Index
- Display Min , Max , Average
- 3.9 Inch display

FEATURES

- Cold Chain Storage
- Data Center
- Hospitals & Restaurant
- Workspace, laboratories
- Residential space
- Office space environmental testing
- Agricultural greenhouses and breeding Laboratory



TECHNICAL SPEC

LCD Display Size	3.9 Inch
Indoor Temperature Range	-30~+65°C Accuracy : $\pm 0.3^\circ\text{C}$ (-10~+65°C)
Indoor Humidity Range	0~100%RH Accuracy : $\pm 3\%$ RH(10~90%RH,25°C)
Units	°C, °F
Measuring Intervals	5 seconds
Response Time	15 minutes
Temp Alert	Yes, For High & Low
Data logging memory	26624 Readings
Power Supply	3 pcs 1.5V AAA alkaline battery
Operating Temperature	-30°C~+65°C
Operating Humidity	0%RH~100%RH
IP Class	IP20
Material	ABS
Product Size	108 x 96 x 20 mm
Net Weight	165g