



Sound and light alarm when over standard

The alarm function will be turned on when the value reaches heavy pollution, the instrument will emit a continuous alarm sound and a red indicator light will be displayed on the top.



Rechargeable lithium battery

Battery life: about 420 minutes , built-in 18650 rechargeable battery 2500mA/h.



Data record

5000 records of data, update once per minute, install the PC software to export or check the data list and trend chart, which can be used to analyze the air quality of the room during the each period.

Features

Real time clock display	✓
Display method	2.8-inch TFT full-view angle true color screen
LCD screen break function	✓
Test mode selection	Choice of single test and simultaneous test
Recording mode selection	Optional continuous recording and timed recording
Storage capacity display	✓
Maximum storage	5000 groups
Testing standards selection	Optional GB/T 18883-2002 and GB50325-2010 standards
Screen brightness setting	✓
View history records	✓
Real-time trend graph display	✓
Alarm setting	Either media alarm can be selected
Buzzer alarm prompt	√
Light alarm	✓
Data export function	✓
PC data analysis	✓
Battery level display	✓
Rechargeable battery	✓
Power	18650 rechargeable battery (with protection board) 2500mA/h USB DC 5V/2A
Size	146 x 80 x 68mm
Standby time	≥6 hours
Weight	About 260g



